

Revision Date: 26-May-2015 Revision Number: 1

# 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name SUPERSATURATED - ULTRA BLUE

Product Code RF5969 Alternate Product Code XY6410

Product Class WATER THINNED PAINT

ColorBlueRecommended usePaint

Restrictions on use No information available

Rosco Laboratories Inc. 52 Harbor View Avenue Stamford, CT 06902, USA Phone: (203)-708-8900 www.rosco.com

**Emergency Telephone Number(s)** 

CHEMTREC (US): 800-424-9300

CHEMTREC (outside US): (703)-527-3887

### 2. HAZARDS IDENTIFICATION

### Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity	Category 1A
Specific target organ toxicity (repeated exposure)	Category 1

#### Label elements

### Danger

#### Hazard statements

May cause cancer

Causes damage to organs through prolonged or repeated exposure



Appearance liquid Odor little or no odor

Revision Date: 26-May-2015

### **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Do not breathe dust/fume/mist/vapors/spray

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

#### **Precautionary Statements - Response**

If exposed or concerned get medical attention

# **Precautionary Statements - Storage**

Store locked up

# **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

### Hazards not otherwise classified (HNOC)

Not Applicable

#### Other information

No information available

## 3. COMPOSITION INFORMATION ON COMPONENTS

Chemical Name	CAS-No	Weight % (max)
Cristobalite	14464-46-1	10
Diatomaceous silica, flux-calcined	68855-54-9	5
Silica, crystalline	14808-60-7	0.5

### 4. FIRST AID MEASURES

**General Advice** No hazards which require special first aid measures.

Eye Contact Rinse thoroughly with plenty of water for at least 15 minutes and consult a

physician.

Skin Contact Wash off immediately with soap and plenty of water removing all contaminated

clothes and shoes.

**Inhalation** Move to fresh air. If symptoms persist, call a physician.

**Ingestion** Clean mouth with water and afterwards drink plenty of water. Consult a physician

if necessary.

Most Important Symptoms/Effects None known.

Notes To Physician Treat symptomatically.

# 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

**Protective Equipment And Precautions For** 

**Firefighters** 

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent)

Revision Date: 26-May-2015

and full protective gear.

Specific Hazards Arising From The Chemical Closed containers may rupture if exposed to fire or

extreme heat.

Sensitivity To Mechanical Impact No

Sensitivity To Static Discharge No

Flash Point Data

Flash Point (°F)

Flash Point (°C)

Flash Point Method

Not applicable
Not applicable

Flammability Limits In Air

Lower Explosion LimitNot applicableUpper Explosion LimitNot applicable

NFPA Health: 1 Flammability: 0 Instability: 0 Special: Not Applicable

### **NFPA** Legend

0 - Not Hazardous

- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal Precautions** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.

**Other Information** Prevent further leakage or spillage if safe to do so.

**Environmental Precautions** See Section 12 for additional Ecological Information.

Methods For Clean-Up Soak up with inert absorbent material. Sweep up and shovel into suitable

containers for disposal.

### 7. HANDLING AND STORAGE

**Handling** Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or

sanding dust. In case of insufficient ventilation, wear suitable respiratory

equipment.

**Storage** Keep container tightly closed. Keep out of the reach of children.

Revision Date: 26-May-2015

Incompatible Materials No information available

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### **Exposure Limits**

Chemical Name	ACGIH	OSHA
Cristobalite	0.025 mg/m <sup>3</sup> - TWA	respirable - (1/2)(10)/(%SiO2 + 2) mg/m³ TWA
		respirable - (1/2)(250)/(%SiO2 + 5) mppcf TWA
		total dust - (1/2)(30)/(%SiO2 + 2) mg/m³ TWA
Silica, crystalline	0.025 mg/m³ - TWA	respirable - (10)/(%SiO2 + 2) mg/m³ TWA
		respirable - (250)/(%SiO2 + 5) mppcf TWA
		total dust - (30)/(%SiO2 + 2) mg/m <sup>3</sup> TWA

## Legend

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits

OSHA - Occupational Safety & Health Administration Exposure Limits

N/E - Not Established

**Engineering Measures** Ensure adequate ventilation, especially in confined areas.

**Personal Protective Equipment** 

**Eye/Face Protection** Safety glasses with side-shields.

**Skin Protection** Protective gloves and impervious clothing.

**Respiratory Protection** In case of insufficient ventilation wear suitable respiratory equipment.

Hygiene Measures Avoid contact with skin, eyes and clothing. Remove and wash contaminated

clothing before re-use. Wash thoroughly after handling.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance liquid

**Odor** little or no odor

Odor Threshold No information available

 Density (lbs/gal)
 10.6 - 11.0

 Specific Gravity
 1.27 - 1.32

Specific Gravity
pH

1.27 - 1.32
No information available

Viscosity (cps)No information availableSolubilityNo information availableWater SolubilityNo information availableEvaporation RateNo information available

Vapor Pressure
No information available
Vapor Density
No information available

 Wt. % Solids
 45 - 55

 Vol. % Solids
 30 - 40

 Wt. % Volatiles
 45 - 55

 Vol. % Volatiles
 60 - 70

 VOC Regulatory Limit (g/L)
 < 250</td>

 Boiling Point (°F)
 212

Revision Date: 26-May-2015

Boiling Point (°C)100Freezing Point (°F)32Freezing Point (°C)0

Flash Point (°F)

Flash Point (°C)

Flash Point Method

Flammability (solid, gas)

Upper Explosion Limit

Lower Explosion Limit

Not applicable

Not applicable

Not applicable

Not applicable

Autoignition Temperature (°F)

Autoignition Temperature (°C)

Decomposition Temperature (°F)

Decomposition Temperature (°C)

No information available

# 10. STABILITY AND REACTIVITY

Reactivity Not Applicable

Chemical Stability Stable under normal conditions.

Conditions To Avoid Prevent from freezing.

**Incompatible Materials**No materials to be especially mentioned.

Hazardous Decomposition Products

None under normal use.

Possibility Of Hazardous Reactions None under normal conditions of use.

### 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

#### **Product Information**

InhalationNo information availableEye contactNo information availableSkin contactNo information availableIngestionNo information available

**Acute Toxicity** 

Product Information No information available

Information on toxicological effects

Symptoms No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization:No information availableMutagenic EffectsNo information available.Reproductive EffectsNo information available.

Numerical measures of toxicity

Revision Date: 26-May-2015

## The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 940822 mg/kg ATEmix (dermal) 978455 mg/kg

**Acute Toxicity** 

#### Component

Silica, crystalline

LD50 Oral: 500 mg/kg (Rat) vendor data

#### Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

Chemical Name	IARC	NTP	OSHA Carcinogen
	1 - Human Carcinogen		Listed
Cristobalite			
	1 - Human Carcinogen	Known Human	Listed
Silica, crystalline		Carcinogen	

<sup>•</sup> Crystalline Silica has been determined to be carcinogenic to humans by IARC (1) when in respirable form. Risk of cancer depends on duration and level of inhalation exposure to spray mist or dust from sanding the dried paint.

#### Legend

IARC - International Agency for Research on Cancer

NTP - National Toxicity Program

OSHA - Occupational Safety & Health Administration

### 12. ECOLOGICAL INFORMATION

## **Ecotoxicity Effects**

The environmental impact of this product has not been fully investigated.

# **Product Information**

### **Acute Toxicity to Fish**

No information available

### **Acute Toxicity to Aquatic Invertebrates**

No information available

# **Acute Toxicity to Aquatic Plants**

No information available

## Persistence / Degradability

No information available.

# **Bioaccumulation / Accumulation**

No information available.

# **Mobility in Environmental Media**

No information available.

#### **Ozone**

No information available

# Component

## **Acute Toxicity to Fish**

No information available

# **Acute Toxicity to Aquatic Invertebrates**

No information available

### **Acute Toxicity to Aquatic Plants**

No information available

## 13. DISPOSAL CONSIDERATIONS

## Waste Disposal Method Dispose of in accordance with federal, state, provincial, and local regulations.

Local requirements may vary, consult your sanitation department or

state-designated environmental protection agency for more disposal options.

Revision Date: 26-May-2015

## 14. TRANSPORT INFORMATION

**DOT** Not regulated

ICAO / IATA Not regulated

IMDG / IMO Not regulated

### 15. REGULATORY INFORMATION

# **International Inventories**

**TSCA: United States DSL: Canada**Yes - All components are listed or exempt.
Yes - All components are listed or exempt.

### Federal Regulations

#### SARA 311/312 hazardous categorization

Acute Health Hazard

Chronic Health Hazard

Yes
Fire Hazard

No
Sudden Release of Pressure Hazard

No
Reactive Hazard

No

### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

None

Revision Date: 26-May-2015

## Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

None

# State Regulations

### **California Proposition 65**

This product may contain small amounts of materials known to the state of California to cause cancer or reproductive harm.

### State Right-to-Know

Chemical Name	Massachusetts	New Jersey	Pennsylvania
Cristobalite	X	X	X
Diatomaceous silica, flux-calcined			X
Silica, crystalline	X	X	X

# Legend

X - Listed

### 16. OTHER INFORMATION

HMIS Health: 1\* Flammability: 0 Reactivity: 0 PPE: -

### **HMIS Legend**

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- \* Chronic Hazard
- X Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Revision Date: 26-May-2015

Prepared By Product Stewardship Department

Rosco Laboratories Inc. 52 Harbor View Avenue Stamford, CT 06902, USA Phone: (203)-708-8900

Revision Date: 26-May-2015 Revision Summary Not available

#### Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

**END OF SAFETY DATA SHEET**