

Revision Date: 26-May-2015

Revision Number: 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name Product Code Alternate Product Code Product Class Color Recommended use Restrictions on use

SUPERSATURATED - RAW UMBER RF5986 XY6409 WATER THINNED PAINT brown Paint

No information available

Rosco Laboratories Inc. 52 Harbor View Avenue Stamford, CT 06902, USA Phone: (203)-708-8900 www.rosco.com

Emergency Telephone Number(s) CHEMTREC (US): 800-424-9300 CHEMTREC (outside US): (703)-527-3887

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity	Category 1A
Specific target organ toxicity (repeated exposure)	Category 1

Label elements

Danger

Hazard statements

May cause cancer Causes damage to organs through prolonged or repeated exposure



Appearance liquid

Odor little or no odor

Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Do not breathe dust/fume/mist/vapors/spray Wash face, hands and any exposed skin thoroughly after handling Do not eat, drink or smoke when using this product

Precautionary Statements - Response

If exposed or concerned get medical attention

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not Applicable

Other information

No information available

3. COMPOSITION INFORMATION ON COMPONENTS

Chemical Name	CAS-No	Weight % (max)
Cristobalite	14464-46-1	10
Diatomaceous silica, flux-calcined	68855-54-9	5
Carbon black	1333-86-4	5
Silica, crystalline	14808-60-7	0.5

4. FIRST AID MEASURES			
General Advice	No hazards which require special first aid measures.		
Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.		
Skin Contact	Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes.		
Inhalation	Move to fresh air. If symptoms persist, call a physician.		
Ingestion	Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary.		
Most Important Symptoms/Effects	None known.		
Notes To Physician	Treat symptomatically.		
	5. FIRE-FIGHTING MEASURES		

Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Protective Equipment And Precautions For Firefighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.
Specific Hazards Arising From The Chemical	Closed containers may rupture if exposed to fire or extreme heat.
Sensitivity To Mechanical Impact	No
Sensitivity To Static Discharge	No
Flash Point Data Flash Point (°F) Flash Point (°C) Flash Point Method	Not applicable Not applicable Not applicable
Flammability Limits In Air	
Lower Explosion Limit Upper Explosion Limit	Not applicable Not applicable
NFPA Health: 1 Flammability: 0 Insta	bility: 0 Special: Not Applicable
NFPA Legend	

NFPA Legend 0 - Not Hazardous

- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

	6.	ACCIDENTAL RELEASE MEASURES	
Personal Precautions		Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.	
Other Information		Prevent further leakage or spillage if safe to do so.	
Environmental Precautions		See Section 12 for additional Ecological Information.	
Methods For Clean-Up		Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.	
		7. HANDLING AND STORAGE	
Handling		Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.	
Storage		Keep container tightly closed. Keep out of the reach of children.	

Incompatible Materials

No information available

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits

Chemical Name	ACGIH	OSHA	
Cristobalite	0.025 mg/m³ - TWA	respirable - (1/2)(10)/(%SiO2 + 2) mg/m ³ TWA respirable - (1/2)(250)/(%SiO2 + 5) mppcf TWA total dust - (1/2)(30)/(%SiO2 + 2) mg/m ³ TWA	
Carbon black	3.5 mg/m ³ - TWA	3.5 mg/m ³ - TWA	
Silica, crystalline	0.025 mg/m³ - TWA	respirable - (10)/(%SiO2 + 2) mg/m ³ TWA respirable - (250)/(%SiO2 + 5) mppcf TWA total dust - (30)/(%SiO2 + 2) mg/m ³ TWA	

Legend

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits OSHA - Occupational Safety & Health Administration Exposure Limits N/E - Not Established

Engineering Measures	Ensure adequate ventilation, especially in confined areas.	
Personal Protective Equipment		
Eye/Face Protection	Safety glasses with side-shields.	
Skin Protection	Protective gloves and impervious clothing.	
Respiratory Protection	In case of insufficient ventilation wear suitable respiratory equipment.	
Hygiene Measures	Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.	

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	liquid
Odor	little or no odor
Odor Threshold	No information available
Density (lbs/gal)	9.8 - 10.2
Specific Gravity	1.17 - 1.22
pH	No information available
Viscosity (cps)	No information available
Solubility	No information available
Water Solubility	No information available
Evaporation Rate	No information available
Vapor Pressure	No information available
Vapor Density	No information available
Wt. % Solids	30 - 40
Vol. % Solids	20 - 30
Wt. % Volatiles	60 - 70
Vol. % Volatiles	70 - 80

VOC Regulatory Limit (g/L) Boiling Point (°F) **Boiling Point (°C)** Freezing Point (°F) Freezing Point (°C) Flash Point (°F) Flash Point (°C) **Flash Point Method** Flammability (solid, gas) **Upper Explosion Limit** Lower Explosion Limit Autoignition Temperature (°F) Autoignition Temperature (°C) **Decomposition Temperature (°F)** Decomposition Temperature (°C) Partition Coefficient (n-octanol/water)

212 100 32 0 Not applicable No information available No information available No information available No information available No information available

10. STABILITY AND REACTIVITY

< 250

Reactivity	Not Applicable
Chemical Stability	Stable under normal conditions.
Conditions To Avoid	Prevent from freezing.
Incompatible Materials	No materials to be especially mentioned.
Hazardous Decomposition Products	None under normal use.
Possibility Of Hazardous Reactions	None under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Reproductive Effects

Inhalation Eye contact Skin contact Ingestion	No information available No information available No information available No information available		
Acute Toxicity			
Product Information	No information available		
Information on toxicological effects			
Symptoms	No information available		
Delayed and immediate effects as well as chronic effects from short and long-term exposure			
Sensitization: Mutagenic Effects	No information available No information available.		

No information available.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	874355 mg/kg
ATEmix (dermal)	909329 mg/kg

Acute Toxicity

Component

<u>Carbon black</u> LD50 Oral: > 15400 mg/kg (Rat) LD50 Dermal: > 3000 mg/kg (Rabbit) <u>Silica, crystalline</u> LD50 Oral: 500 mg/kg (Rat) vendor data

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

Chemical Name	IARC	NTP	OSHA Carcinogen
	1 - Human Carcinogen		Listed
Cristobalite	Ŭ		
	2B - Possible Human		Listed
Carbon black	Carcinogen		
	1 - Human Carcinogen	Known Human	Listed
Silica, crystalline		Carcinogen	

• Crystalline Silica has been determined to be carcinogenic to humans by IARC (1) when in respirable form. Risk of cancer depends on duration and level of inhalation exposure to spray mist or dust from sanding the dried paint.

Legend

IARC - International Agency for Research on Cancer NTP - National Toxicity Program OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

Product Information

Acute Toxicity to Fish No information available

Acute Toxicity to Aquatic Invertebrates

No information available

<u>Acute Toxicity to Aquatic Plants</u> No information available

Persistence / Degradability

No information available.

Bioaccumulation / Accumulation

No information available.

Mobility in Environmental Media

No information available.

<u>Ozone</u>

No information available

Component

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

	13. DISPOSAL CONSIDERATIONS		
Waste Disposal Method	Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.		
	14. TRANSPORT INFORMATION		
DOT	Not regulated		
ICAO / IATA	Not regulated		
IMDG / IMO	Not regulated		
	15. REGULATORY INFORMATION		
International Inventories			
TSCA: United States DSL: Canada	Yes - All components are listed or exempt. Yes - All components are listed or exempt.		
Federal Regulations			
SARA 311/312 hazardous categ			
Acute Health Hazard	No		

Acute Health Hazard	No
Chronic Health Hazard	Yes
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

None

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

None

State Regulations

California Proposition 65

This product may contain small amounts of materials known to the state of California to cause cancer or reproductive harm.

State Right-to-Know

Chemical Name	Massachusetts	New Jersey	Pennsylvania
Cristobalite	Х	X	Х
Diatomaceous silica, flux-calcined			Х
Carbon black	Х	X	Х
Silica, crystalline	Х	X	Х

Legend

X - Listed

16. OTHER INFORMATION

HMIS	Health: 1*	Flammability: 0	Reactivity: 0	PPE: -	
HMIS Lege) - Minimal H 1 - Slight Ha. 2 - Moderate 3 - Serious H 4 - Severe H 5 - Chronic H	lazard zard Hazard lazard azard				
		O.P. for "Special" handling	instructions.		

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Prepared By	Product Stewardship Department Rosco Laboratories Inc. 52 Harbor View Avenue Stamford, CT 06902, USA Phone: (203)-708-8900
Revision Date:	26-May-2015
Revision Summary	Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

END OF SAFETY DATA SHEET